

Circulator for OEMs

Calio SI HP MINI / HP MINI Therm

Type Series Booklet



Legal information/Copyright

Type Series Booklet Calio SI HP MINI / HP MINI Therm

Original operating manual

All rights reserved. The contents provided herein must neither be distributed, copied, reproduced, edited or processed for any other purpose, nor otherwise transmitted, published or made available to a third party without the manufacturer's express written consent.

Subject to technical modification without prior notice.

© KSB Pompa Armatür San. ve Tic. A.Ş., Türkiye 02/12/2019

Contents

Building Services: Heating	4
Variable Speed Circulator Pumps	4
Calio SI HP MINI 25-130 PWM	4
Main applications	4
Fluids handled	4
Operating data	4
Designation	4
Design details	4
Materials	4
Product benefits	4
Certifications	5
FluidFuture energy efficiency concept developed by KSB	5
Technical data	5
PWM signal	5
Characteristic curves	6
Dimensions	7
Installation information	7
Scope of supply	7
Connecting the power cable	7

Building Services: Heating

Variable Speed Circulator Pumps

Calio SI HP MINI 25-130 PWM



Main applications

Heating, ventilation, air-conditioning and circulation systems

- Underfloor heating systems
- Boiler or primary circuits
- Solar power systems
- Heat pumps

Transfer stations and similar

Fluids handled

- Heating water to VDI 2035. If the glycol content equals or exceeds 50 %, check and verify the operating data.
- Pure, thin, non-aggressive and non-explosive fluids not containing any mineral oil, solids or long fibers

Operating data

Operating properties

Characteristic		Value
Flow rate	Q [m³/h]	4
Head	H [m]	9,5
Fluid temperature	T [°C]	-10 to +110
Ambient temperature	T [°C]	0 to 55
Operating pressure	p [bar]	10
Sound pressure level	[dB (A)]	≤ 30
Connection	G2 ½	

Designation

Example: Calio SI HP MINI 25-130 PWM

Designation key

Code	Description	
Calio SI HP Mini	Type series	
25	Nominal diameter of pipe connection	
	25	G1 ½
130	Overall length 130 mm	

Design details

Design

- Highly efficient, maintenance-free wet rotor pump (glandless)
- Screw-ended

Drive

- Brushless permanent magnet motor, self-cooling
- 230 V - 50/60 Hz
- Inrush current < 3 A
- Thermal class F
- IP44 enclosure
- Temperature class TF 110
- Interference emission EN 55014-1
- Interference immunity EN 55014-2
- IEC 60335-2-51

Bearings

- Ceramic bearing

Operating modes

- Pump speed control via external PWM signal

Materials

Overview of available materials

Component	Material
Volute casing	Grey cast iron/Stainless
Shaft	Ceramics
Impeller	Plastic with glass fibers content (PA - GF 35)
Bearing	Ceramics
Bearing plate	Stainless steel 1.4401
Can	Stainless steel 1.4401

1) In the boiler

Certifications

Overview

Label	Valid in:	Comment
	Europe	EEI ≤ 0.21

Technical data

Selection table

Size	Connection		PN	P ₁ [W]	Motor protection	Signalling contacts	Nominal current 1~230 VAC, 50/60 Hz [A]
	Pipeline	Pump					
HP Mini 25-180 PWM	R1	G1 ½	10	150	X	PWM / 0 - 10 V	0,1 - 1
HP Mini Therm 25-180 PWM	R1	G1 ½	10	150	X	PWM / 0 - 10 V	0,1 - 1
HP Mini 25-130 PWM	R1	G1 ½	10	150	X	PWM / 0 - 10 V	0,1 - 1

Operation controlled by external input

PWM signal

The pump set communicates with an external control system via a pump-integrated 2-way PWM interface. The pump sends the flow rate Q to the external control system and, in return, receives the maximum required differential pressure. The pump control system adjusts the speed to achieve the required differential pressure. Profile A for heating applications is stored in the pump software as standard. If no PWM signal is connected, the pump set is operated at maximum speed.

PWM profiles available for selection:

- Profile A for heating applications
- Profile C for solar applications

Operation controlled by PWM profile A (heating applications)

Parameters / statuses sent

Parameter / function	PWM signal [%]	Comments
Parameters / statuses sent by external control system		
Maximum speed	99 - 100	No PWM signal connected: The pump set is operated at maximum speed
Pump ID	0 - 4	-
Modulation	5 - 91	-
Stand-by	94 - 98	Pump set can still be controlled.




Fig. 2: PWM profile A, PWM signal from pump control system to external control system

Parameter / statuses sent by pump set

Parameter / function	PWM signal [%]	Comments
Parameters / statuses sent by external control system		
Pump ID	85	-
Blocked rotor	75	-
Modulation	20-70	Estimated flow rate
Dry running	10	-

Operation controlled by PWM profile C (solar applications)

Parameter / function	PWM signal [%]	Comments
Parameters / statuses sent by external control system		
Maximum speed	91 - 99	No PWM signal connected: Pump set stops.
Pump ID	0 - 4	-
Modulation	5 - 91	-
Stand-by	94 - 98	Pump set can still be controlled.






Fig. 3: PWM profile C, PWM signal from the pump to the external control system

Parameter / statuses sent by pump set

Parameter / function	PWM signal [%]	Comments
Parameters / statuses sent by external control system		
Pump ID	85	-
Blocked rotor	75	-
Modulation	20-70	Estimated flow rate
Dry running	10	-

Characteristic curves


Calio SI HP MINI 25-130/180 PWM



Constant curve (25-130)

Dimensions

Calio SI HP MINI 25-130 PWM




Dimensions

Size	R	G	H
HP Mini 25-180 PWM	R1	G1 1/2	180
HP Mini Therm 25-180 PWM*	R1	G1 1/2	180
HP Mini 25-130 PWM	R1	G1 1/2	130

*Stainless Steel

Calio SI HP MINI


Permissible installation positions

Sizes	
All	

Scope of supply



- Pump
- Connection socket for main supply 230 V
- Communication Cable

Connecting the power cable



Connecting the cores at the contact insert

L	Conductor / phase (230 V)
N	Neutral conductor
⏏	Earthing





KSB SE & Co. KGaA
67225 Frankenthal • Johann-Klein-Str. 9 • 67227 Frankenthal (Germany)
Tel. +49 6233 86-0 • Fax +49 6233 86-3401
www.ksb.com